

# MATERIAL SAFETY DATA SHEET

2613

Required under USDL Safety and Health Regulations for Ship Repairing,  
Shipbuilding, and Shipbreaking (29 CFR 1915, 1916, 1917)

## SECTION I

MANUFACTURER'S NAME Dataproducts Corporation		EMERGENCY TELEPHONE NO. 404-447-4766
ADDRESS (Number, Street, City, State, and ZIP Code) 5985 Financial Drive, Norcross, GA 30071		
CHEMICAL NAME AND SYNONYMS N/A	TRADE NAME AND SYNONYMS Apple Imagewriter/IW II	
CHEMICAL FAMILY N/A	FORMULA N/A	

## SECTION II - HAZARDOUS INGREDIENTS

PAINTS, PRESERVATIVES, & SOLVENTS	%	TLV (Units)	ALLOYS AND METALLIC COATINGS	%	TLV (Units)
PIGMENTS	N/A		BASE METAL	N/A	
CATALYST	N/A		ALLOYS	N/A	
VEHICLE	N/A		METALLIC COATINGS	N/A	
SOLVENTS	N/A		FILLER METAL PLUS COATING OR CORE FLUX	N/A	
ADDITIVES	N/A		OTHERS	N/A	
OTHERS	N/A				
HAZARDOUS MIXTURES OF OTHER LIQUIDS, SOLIDS, OR GASES				%	TLV (Units)
Contains no known hazardous ingredients.					

## SECTION III - PHYSICAL DATA

BOILING POINT (°F.)	N/A	SPECIFIC GRAVITY (H <sub>2</sub> O=1)	N/A
VAPOR PRESSURE (mm Hg.)	N/A	PERCENT VOLATILE BY VOLUME (%)	Less Than 1%
VAPOR DENSITY (AIR=1)	N/A	EVAPORATION RATE (_____ =1)	N/A
SOLUBILITY IN WATER	N/A		
APPEARANCE AND ODOR Plastic cassette with inked ribbon, odor: slightly rubber like.			

## SECTION IV - FIRE AND EXPLOSION HAZARD DATA

FLASH POINT (Method used)	Greater than 200° F.	FLAMMABLE LIMITS	Lel	Uel
EXTINGUISHING MEDIA	CO <sub>2</sub> , Foam or Dry Chemical. Treat as Class B Fire			
SPECIAL FIRE FIGHTING PROCEDURES	Use self contained breathing apparatus. Personal protective equipment may be needed for large fire.			
UNUSUAL FIRE AND EXPLOSION HAZARDS	None known			

SECTION V - HEALTH HAZARD DATA	
THRESHOLD LIMIT VALUE	N/A
EFFECTS OF OVEREXPOSURE	Prolonged oral contact may cause acute health effects in some individuals.
EMERGENCY AND FIRST AID PROCEDURES	Remove ribbon cassette and provide medical attention.

SECTION VI - REACTIVITY DATA			
STABILITY	UNSTABLE		CONDITIONS TO AVOID
	STABLE	X	Temperatures in excess of 200° F.
INCOMPATIBILITY (Materials to avoid) Strong oxidizers and strong acids.			
HAZARDOUS DECOMPOSITION PRODUCTS			
HAZARDOUS POLYMERIZATION	MAY OCCUR		CONDITIONS TO AVOID
	WILL NOT OCCUR	X	

SECTION VII - SPILL OR LEAK PROCEDURES	
STEPS TO BE TAKEN IN CASE MATERIAL IS RELEASED OR SPILLED	Remove ribbon cassettes from all floor areas to allow for stable footing and prevent slips by personnel.
WASTE DISPOSAL METHOD	May be disposed of in a sanitary landfill licensed to receive non-hazardous waste

SECTION VIII - SPECIAL PROTECTION INFORMATION			
RESPIRATORY PROTECTION (Specify type)			
N/A			
VENTILATION	LOCAL EXHAUST	N/A	SPECIAL
	MECHANICAL (General)	N/A	OTHER
		N/A	N/A
PROTECTIVE GLOVES		N/A	EYE PROTECTION
		N/A	N/A
OTHER PROTECTIVE EQUIPMENT			
N/A			

SECTION IX - SPECIAL PRECAUTIONS	
PRECAUTIONS TO BE TAKEN IN HANDLING AND STORING	Do not store above 200° F.
OTHER PRECAUTIONS	Wash hands with soap and water before eating or smoking.

Note: This is typical data based on information furnished by our suppliers of raw materials. Typical data should not be construed as a guaranteed analysis of the product or as a specification for the product.