

iMac (Retina 5K, 27-inch, 2017)

iMac (Retina 5K, 27-inch, 2019)

iMac (Retina 5K, 27-inch, 2020)

# Apple Recycler Guide

July 2023

### **Contents**

- 3 About This Guide
- 4 Identification
- 5 Directive 2012/19/EU Annex VII Components
- 6 Safety Considerations
- 7 Recommended Tools
- 8 Disassembly Instructions
- 32 Material Categorization of Output Fractions

### **About This Guide**

Apple Recycler Guides provide guidance for electronics recyclers on how to disassemble products to maximize recovery of resources. The guides provide step-by-step disassembly instructions and information on the material composition to help recyclers direct fractions to the appropriate material recycler.

To conserve important resources, we work to reduce the materials we use and aim to one day source only recycled or renewable materials in our products. A key path to reaching that goal is resource recovery from end-of-life electronics.


Disassembly procedures are intended to be performed only by trained electronics recycling professionals. The recycler is responsible for independently evaluating and ensuring compliance with all applicable environmental, health, and safety laws related to the work. These include but are not limited to laws relating to the management, handling, shipping, and disposal of the outputs of this work as waste and laws in place to ensure the health and safety of all employees who support this work.

For questions or feedback about this guide, email contactesci@apple.com.

**Note:** This guide may show images from other similar models, but the procedures are the same.

### Identification

You can find the model number of the iMac on the bottom of the stand.



Model numbers: A1419, A2115

## Directive 2012/19/EU Annex VII Components

Directive 2012/19/EU Annex VII requirements apply to the following substances and components.

Substance/Component	Apple Part Name	Removal Instructions
Printed circuit board if the surface is greater than 10 square centimeters	Hard drive, display logic board, light-emitting diode (LED) logic board, power supply, main logic board	Follow steps 1–18
External electric cables	Power cord	Follow step 1
Battery	Coin cell battery	Follow steps 1–17
Cover glass and liquid crystal display (LCD) cell if the surface is greater than 100 square centimeters	Display	Follow steps 1–8
No further substances or components as listed in Annex VII		

### **Safety Considerations**

The recycler is responsible for independently evaluating all activities undertaken by its employees to perform or support the work and ensuring compliance with all applicable health and safety laws related to the work. These include but are not limited to laws relating to the health and safety of all employees who perform or support this work. The recycler is also responsible for evaluating the workspace and ensuring that the area in which the work is to be undertaken is designed using ergonomic best practices and meets all ergonomic requirements to ensure the protection of its employees.

### Personal Protective Equipment

Personal protective equipment should be worn during the entire recycling process.



Wear hand protection



Wear a mask



Wear eye protection



Wear foot protection



Wear protective clothing

### **LED Safety**

Broken LEDs must be handled properly to ensure the safety of your employees and mitigate any hazards. Package broken LEDs in an appropriate container to properly manage the hazards associated with the materials and store only with compatible materials. All waste must be properly classified, packaged, and labeled in accordance with all relevant laws and regulations.

### Hazard Warnings



Broken glass hazard



Chemical inhalation hazard



Chemical exposure hazard

### **Recommended Tools**




## **Disassembly Instructions**


### 1. Remove the power cord.

>> Ensure that the iMac is turned off.




>> Unplug the power cord from the back of the iMac.






**Warning:** Before continuing disassembly, wait 10 minutes after unplugging the device for stored energy to discharge.

# **2.** Pry the display away from the housing.




# **3.** Separate the display from the housing.


>> Disconnect the wires by hand.




>> Lay the display facedown. Set the housing aside.




4. Pull the ribbon cables off the back of the display.




**5.** Pry off the display logic board cover.







**6.** Pry off the display logic board.







**7.** Pull the cable off the display mid plate.






### 8. Remove the LCD cell and display films.


>> Pry the mid plate off the LCD cell and films. Set the mid plate aside.






>> Lift the display films away from the LCD cell.








### **9.** On the mid plate, remove the LED logic board.




Chemical inhalation hazard


>> Unscrew the 16 Phillips fasteners along the length of the LED logic board cover.









Separate the LED cover from the LED logic board using the miniature pry bar.






# **10.** Inside the housing, remove the left speaker.

>> Pry off the speaker.



>> Cut the cable that attaches the speaker to the main logic board.









### **11.** Remove the hard drive.


>> Unplug the hard drive/main logic board connector.






 $\ensuremath{\boldsymbol{\mathcal{Y}}}$  Pry the hard drive off the brackets.






# **12.** Remove the hard drive brackets.






# **13.** Pry off the fan.









## **14.** Remove the power supply logic board.


>> Unscrew the four Torx T8 fasteners.




>> Flip over the power supply logic board and cut the two cables.











# **15.** Remove the right speaker.


>> Pry off the speaker.






>> Cut the cable that attaches the speaker to the main logic board.






# **16.** Remove the main logic board.

>> Pry the main logic board off the housing.






>> Flip over the main logic board and pry it off the heat sink.




**17.** Remove the coin cell battery from the main logic board.










18. Pull the four cables off the main logic board.









# **19.** Pull the hard drive/main logic board connector off the housing.







# **20.** Remove the heat sink from the housing by unscrewing the three Torx T8 fasteners.








# **21.** Pry off the three Wi-Fi antennas.



Tools Used

# **22.** Remove the camera with logic board.


>> Pull off the ribbon cable by hand.










ightharpoonup Pry off the camera with logic board.






# **23.** Pry off the microphone.







## **24.** Pry off the Bluetooth antenna.










# **25.** Remove the stand by unscrewing the nine Torx T8 fasteners.







# **26.** Remove the hinge from the housing by unscrewing the six Torx T8 fasteners.






# **27.** Pry off the headphone jack.






Headphone jack


# **28.** Pry off the power connector.






# **29.** Pry off the power button.










### **Material Categorization of Output Fractions**

All outputs from this process must be managed, handled, and disposed of in accordance with applicable waste laws and regulations, including but not limited to the Waste Framework Directive and its national enactments in Europe.



Coin cell battery

#### **Downstream Processing**

#### **Ferrous**



Display logic board cover



Hard drive brackets





Fasteners (x38)



Hinge

### **Primary Target Material**



#### Glass



LCD cell

#### **Primary Target Material**







#### **Downstream Processing**

#### **Hard Drives**



Hard drive

### **Primary Target Material**











#### **Downstream Processing**

### **Logic Boards**



Display logic board

LED logic board



Power supply logic board



Main logic board



Camera with logic board

### **Primary Target Material**











#### **Mixed Electronics**



Fan



Power cord



Cables



Hard drive/main logic board connector



Heat sink



### **Primary Target Material**









### **Mixed Electronics (cont.)**



Microphone





Wi-Fi and Bluetooth antennas



Headphone jack



Power connector



Power button

#### **Mixed Plastics**



Display films

LED cover

#### **Primary Target Material**



### **Downstream Processing**

#### **Rare Earth Magnets**



Left speaker



Right speaker

### **Primary Target Material**







